



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 1/11

**SECTION 1: IDENTIFICATION****GHS product identifier:** Paint / Primer Products**Recommended use of the chemical and restrictions on use:** Veneer Birch, Maple, Euro Birch, Medium Density Fiberboard**Supplier's details:** USply LLC  
9400 NW 104th Street, #100  
Medley, FL 33178  
Phone#: +1 (305) 722-6622  
www.usply.net**Emergency phone number:** +1 (305) 722-6622**SECTION 2: HAZARD IDENTIFICATION****Classification of the substance or mixture:** Flammable Liquids - Category 4;  
Skin Corrosion/Irritation - Category 2;  
Serious eye damage/eye irritation - Category 2A;  
Skin Sensitization - Category 1;  
Germ Cell Mutagenicity - Category 1B;  
Carcinogenicity - Category 1B;  
Hazardous to the Aquatic Environment - Acute Hazard - Category 2.  
**Classification system adopted:** Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.**GHS label elements, including precautionary statements****Pictograms:****Signal word:** DANGER**Hazard statement(s):** H227 Combustible liquid.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H401 Toxic to aquatic life.**Precautionary statement(s):** **PREVENTION:**  
P203 Obtain, read and follow all safety instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 2/11

P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

**RESPONSE TO EMERGENCY:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P318 IF exposed or concerned, get medical advice.

P321 Specific treatment.

P332 + P317 If skin irritation occurs: Get medical help.

P333 + P317 If skin irritation or rash occurs: Get medical help.

P337 + P317 If eye irritation persists: Get medical help.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use carbon dioxide (CO<sub>2</sub>), foam, water mist and powder to extinguish.

**STORAGE:**

P403 Store in a well-ventilated place.

P405 Store locked up.

**DISPOSITION:**

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification: The product has no other hazards.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****MIXTURE**

Components contributing to the hazard:

Product identifier	CAS/EC	Concentration range (%)
Trimethylolpropane triacrylate	15625-89-5 239-701-3	7.42 - 8.20
Methyl isobutyl ketone	108-10-1 203-550-1	5.49 - 6.07
2,2-bis(((1-oxoallyl) oxi) metil) -1,3-propanodiilo diacrilato; ácido 2-propenóico, 1,1'- (2,2-bis-(((1-oxo-2-propen-1-il) oxi) metil) -1,3 - propanodiiil) éster	4986-89-4 225-644-1	4.66 - 5.15
Polyester acrylate	607391-96-8 642-374-3	4.53 - 5.01
Glycerol, propoxylated, esters with acrylic acid	52408-84-1 500-114-5	3.56 - 3.93
2-Hydroxy-2-methylpropiophenone	7473-98-5 231-272-0	3.52 - 3.89
Pentaerythryl triacrylate	3524-68-3 222-540-8	3.20 - 3.53
2,2-dimethyltrimethylene diacrylate	2223-82-7 218-741-5	2.09 - 2.31



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 3/11

Butyl acetate	123-86-4 204-658-1	0.86 - 0.94
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9	0.77 - 0.85
Xylene	1330-20-7 215-535-7	0.74 - 0.82
8E887 Polyurethane High molecular block polymer from DISPERBYK-2150	935-869-3	0.40 - 0.44
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0	0.29 - 0.32
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide <sup>1</sup>	162881-26-7 423-340-5	0.06 - 0.07
Methyl benzoylformate <sup>1</sup>	15206-55-0 239-263-3	0.04 - 0.05
2-Phenoxyethyl acrylate <sup>1</sup>	48145-04-6 256-360-6	0.02 - 0.03
4-methoxyphenol <sup>1</sup>	150-76-5 205-769-8	0.007
Ethoxylated trimethylolpropane triacrylate <sup>1</sup>	28961-43-5 500-066-5	0.003
Butylated hydroxytoluene	128-37-0 204-881-4	0.001

<sup>1</sup> The ingredient does not contribute to the hazard, but is classified as a sensitizer.

**SECTION 4: FIRST-AID MEASURES****Description of necessary first-aid measures**

Inhalation:	Remove victim to fresh air and keep in a position that does not obstruct breathing. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Skin:	Wash exposed skin with sufficient amount of water to remove the product. Remove and isolate contaminated clothing and shoes. In case of skin irritation: Consult a doctor. Bring this document.
Eye:	Rinse carefully with water for several minutes. If wearing contact lenses, remove them if it is easy and keep rinsing. If eye irritation persists: consult a doctor. Bring this document.
Ingestion:	Wash the victim's mouth with plenty of water. Never give anything by mouth to an unconscious person. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Most important symptoms/effects, acute and delayed:	May cause an allergic skin reaction with pruritus and dermatitis. Causes skin irritation with redness, pain and dryness. Causes serious eye irritation with redness and pain.
Indication of immediate medical attention and special treatment needed, if necessary:	Avoid contact with the product when helping the victim. If necessary, symptomatic treatment should include, above all, supportive measures such as correction of hydro electrolytic and metabolic disorders and respiratory assistance. In case of skin contact, do not rub the affected area.

**SECTION 5: FIRE-FIGHTING MEASURES**

**SAFETY DATA SHEET****Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 4/11

Extinguishing media:	Suitable: carbon dioxide (CO <sub>2</sub> ), foam, water mist and powder. Unsuitable: water jet directly.
Specific hazards arising from the chemical:	Combustion of the material or its packaging can form irritating and toxic gases such as carbon monoxide and dioxide. Vapors can be denser than air and tend to accumulate in low-lying or confined areas such as storm drains and basements. Containers may explode if heated.
Special protective actions for fire-fighters:	Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing. Containers and tanks involved in the fire must be cooled with water mist.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel:	Isolate the leakage from sources of ignition. Keep unauthorized persons away from the area. Stop the leakage if it can be done without risk. Do not smoke. Do not touch damaged containers or spilled product without proper clothing. Avoid exposure to the product. Stay in a safe place, with the wind at your back. Use personal protective equipment as described in section 8.
For emergency responders:	Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.
Environmental precautions:	Avoid that the spilled product reaches waterways or sewage system.
Methods and materials for containment and cleaning up:	Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural or spill containment barriers. Collect spilled products and place them in appropriate containers. Adsorb the remaining product with dry sand, earth, vermiculite, or any inert product. Place the adsorbed product in proper containers and remove it to a safe place. For final disposal, proceed according to Section 13 of this document.

**SECTION 7: HANDLING AND STORAGE****Precautions for safe handling**

Precautions for safe handling:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation. Avoid exposure to the product, since the effects may not be felt immediately. Use personal protective equipment as described in section 8. Avoid contact with incompatible materials.
General hygiene:	Wash hands and face thoroughly after handling and before eating, drinking, smoking, or using the toilet. Contaminated clothing should be changed and washed before reuse. Remove contaminated clothing and protective equipment before entering eating areas.

**Conditions for safe storage, including any incompatibilities**

Technical measures for prevention of fire and explosion:	It is not expected that the product presents a fire or explosion hazard.
Conditions for safe storage, including any incompatibilities:	Store in a dry, well-ventilated place away from sunlight. Keep the container closed. It is not necessary addition of stabilizers and antioxidants to ensure the durability. This material may react dangerously with some incompatible materials as outlined in Section 10. Keep away from incompatible materials.
Packaging compatibilities:	Similar to the original packaging.
Inadequate packaging materials:	There are not known unsuitable material.



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 5/11

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters**

Occupational exposure limit: The values below apply to workplaces.

- Titanium dioxide:

OSHA - PEL - TWA: 15 mg/m<sup>3</sup> (TD) (29 CFR 1910.1000 Table Z-1) (CFR);

NIOSH - REL - TWA: (Ca.AA);

ACGIH - TLV - TWA: 0.2 mg/m<sup>3</sup> (NP.R); 2.5 mg/m<sup>3</sup> (FP.R);

- Methyl isobutyl ketone:

OSHA - PEL - TWA: 100 ppm (410 mg/m<sup>3</sup>) (29 CFR 1910.1000 Table Z-1) (CFR);

NIOSH - REL - TWA: 50 ppm (205 mg/m<sup>3</sup>);

NIOSH - REL - STEL: 75 ppm (300 mg/m<sup>3</sup>);

ACGIH - TLV - TWA: 20 ppm;

ACGIH - TLV - STEL: 75 ppm;

- Silicon dioxide:

OSHA - PEL - TWA: 20 mppcf (80 mg/m<sup>3</sup>)/(%SiO<sub>2</sub>) (29 CFR 1910.1000 Table Z-3. Mineral Dusts) (CFR);

NIOSH - REL - TWA: 6 mg/m<sup>3</sup>;

- Talc:

OSHA - PEL - TWA: 20 mppcf (29 CFR 1910.1000 Table Z-3, Mineral Dusts) (CFR);

NIOSH - REL - TWA: 2 mg/m<sup>3</sup> (R);

ACGIH - TLV - TWA: 2 mg/m<sup>3</sup> (E) (R);

- Butyl acetate:

OSHA - PEL - TWA: 150 ppm (710 mg/m<sup>3</sup>) (29 CFR 1910.1000 Table Z-1) (CFR);

NIOSH - REL - TWA: 150 ppm (710 mg/m<sup>3</sup>);

NIOSH - REL - STEL: 200 ppm (950 mg/m<sup>3</sup>);

ACGIH - TLV - TWA: 50 ppm;

ACGIH - TLV - STEL: 150 ppm;

- Xylene:

OSHA - PEL - TWA: 100 ppm (435 mg/m<sup>3</sup>) (29 CFR 1910.1000 Table Z-1) (CFR);

NIOSH - REL - TWA: 100 ppm (435 mg/m<sup>3</sup>);

NIOSH - REL - STEL: 150 ppm (655 mg/m<sup>3</sup>);

ACGIH - TLV - TWA: 20 ppm;

- Zinc stearate:

OSHA - PEL - TWA: 5 mg/m<sup>3</sup> (R); 15 mg/m<sup>3</sup> (TD);

NIOSH - REL - TWA: 10 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);

ACGIH - TLV - TWA: 10 mg/m<sup>3</sup> (I); 3 mg/m<sup>3</sup> (R).

TD: Total dust;

R: Respirable particulate matter;

Ca: Potential occupational carcinogen.

AA: See NIOSH REL Appendix A;

NP: Nanoscale particles;

FP: Finescale particles;

CFR: See mentioned item in OSHA CFR;

mppcf: Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors - mppcf X 35.3 = million particles per cubic meter = particles per c.c.

E: The value is for particulate matter containing no asbestos and < 1% crystalline silica;

I: Inhalable particulate matter.



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 6/11

Biological limit:	- <u>Methyl isobutyl ketone:</u> ACGIH - BEI: Determinant: Methyl isobutyl ketone in urine. Sampling Time: End of shift. Index: 1 mg/L.
	- <u>Xylene:</u> ACGIH - BEI: Determinant: Methylhippuric acid in urine. Sampling Time: End of shift. Index: 0.3 g/g creatinine.
Other limits and values:	- <u>Methyl isobutyl ketone:</u> IDLH: 500 ppm
	- <u>Titanium dioxide:</u> IDLH (NIOSH, 2010): 5000 mg/m <sup>3</sup>
	- <u>Talc:</u> NIOSH (IDLH): 1000 mg/m <sup>3</sup> .
Appropriate engineering controls:	A risk assessment is recommended to define the engineering control measures necessary to eliminate or minimize the risk. These measures help to reduce exposure to the product. Maintain atmospheric concentrations of the constituents of the material below occupational exposure limits indicated.
<b>Individual protection measures, such as personal protective equipment (PPE)</b>	
Eye/face protection:	Protective glasses.
Skin protection:	Closed shoes and appropriate protective clothing. Suitable protective gloves.
Respiratory protection:	A risk assessment should be performed for proper definition of respiratory protection, in view of the material use conditions.
Thermal hazards:	It does not present thermal hazards.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical state:	Liquid.
Colour:	Not available.
Odour:	Not available.
Melting point/freezing point:	Not available.
Boiling point or initial boiling point and boiling range:	Not available.
Flammability:	Combustible.
Lower and upper explosion limit/flammability limit:	Not available.
Flash point:	> 60 °C (140 °F) and ≤ 93 °C (199.4 °F) - Closed cup.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
pH:	Not available.



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 7/11

Kinematic viscosity:	Not available.
Solubility:	Immiscible in water.
Partition coefficient n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.
Density and/or relative density:	Absolute density: 1.05 to 1.77 g/cm <sup>3</sup> at 25 °C (77 °F).
Relative vapour density:	Not available.
Particle characteristics:	Not applicable.
Other information:	Not applicable.

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity:	Reactivity is not to be expected under normal conditions of temperature and pressure.
Chemical stability:	Stable under normal temperature and pressure conditions.
Possibility of hazardous reactions:	- <u>Methyl isobutyl ketone</u> : May form unstable and explosive peroxides in contact with air. - <u>Pentaerythrityl triacrylate</u> : It suffers easy polymerization. - <u>2,2-dimethyltrimethylene diacrylate</u> : Reacts readily with electrophilic agents, free radicals and nucleophiles. Can polymerize. - <u>Xylene</u> : Risk of explosion when in contact with nitric acid and uranium hexafluoride. May react dangerously with oxidizing agents, acids and sulfuric acid. - <u>Butylated hydroxytoluene</u> : Dust can form explosive mixture with air.
Conditions to avoid:	High temperatures. Contact with incompatible materials.
Incompatible materials:	Acid anhydrides, acid chlorides, acids, aluminum powder, calcium, lithium, magnesium, nitric acid, oxidizing agents, oxygen, peroxides, potassium, reducing agents, sodium, strong acids, strong base, strong oxidizing agents, sulphuric acid, uranium hexafluoride and zinc powder.
Hazardous decomposition products:	No dangerous decomposition products are known.

**SECTION 11: TOXICOLOGICAL INFORMATION**

Acute toxicity:	Product not classified as acute toxic. ATEmix Oral: > 5000 mg/kg. ATEmix Dermal: > 5000 mg/kg. ATEmix Vapours (4h): > 20 mg/L. ATEmix Dusts and mists (4h): > 5 mg/L.
Skin corrosion/irritation:	Causes skin irritation with redness, pain and dryness.



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 8/11

Serious eye damage/  
irritation:

Causes serious eye irritation with redness and pain.

Respiratory or skin  
sensitization:May cause an allergic skin reaction with pruritus and dermatitis.  
It is not expected to cause respiratory sensitization.

The ingredients Pentaerythrityl triacrylate, 2,2-bis(((1-oxoallyl) oxi) metil) -1,3-propanodiilo diacrilato; ácido 2-propenóico, 1,1' - (2,2-bis-(((1-oxo-2-propen-1-il) oxi) metil) -1,3 - propanodiil) éster, Trimethylolpropane triacrylate, Glycerol, propoxylated, esters with acrylic acid, 2,2-dimethyltrimethylene diacrylate and Polyester acrylate are classified as skin sensitizers and contribute to this product classification.

The ingredients Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, Ethoxylated trimethylolpropane triacrylate, 4-methoxyphenol, Methyl benzoylformate and 2-Phenoxyethyl acrylate, classified as skin sensitizers - category 1, are in concentrations < 1% and do not contribute to this classification of the product.

Germ cell mutagenicity:

May cause genetic defects.

Carcinogenicity:

May cause cancer.

Reproductive toxicity:

It is not expected to be reproductively toxic.

The ingredient Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide, classified as reproductive toxicant - category 2, is in concentration < 3% and does not contribute to this classification of the product.

STOT - Single  
exposure:

It is not expected to exhibit specific target organ toxicity by single exposure.

STOT - Repeated  
exposure:

It is not expected to exhibit specific target organ toxicity on repeated exposure.

Aspiration hazard:

It is not expected to present an aspiration hazard.

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Toxic to aquatic life.

Information regarding to:

- Trimethylolpropane triacrylate:LC<sub>50</sub> (*Danio rerio*, 96 h): 0.87 mg/L;ErC<sub>50</sub> (*Desmodesmus subspicatus*, 96 h): 18.8 mg/L;EC<sub>50</sub> (*Daphnia magna*, 48 h): 19.9 mg/L.- Glycerol, propoxylated, esters with acrylic acid:ErC<sub>50</sub> (*Desmodesmus subspicatus*, 72 h): 12.2 mg/L;LC<sub>50</sub> (*Danio rerio*, 96 h): 5.74 mg/L;EC<sub>50</sub> (*Daphnia magna*, 48 h): 91.4 mg/L.- 2-Hydroxy-2-methylpropiophenone:EC<sub>50</sub> (*Daphnia magna*, 48 h): > 100 mg/L;NOEC (*Desmodesmus subspicatus*, 72 h): 0.194 mg/L;ErC<sub>50</sub> (*Desmodesmus subspicatus*, 72 h): 1.95 mg/L.- Butylated hydroxytoluene:LC<sub>50</sub> (*Danio rerio*, 96 h): = 0.57 mg/L;ErC<sub>50</sub> (*Desmodesmus subspicatus*, 72 h): > 0.4 mg/L;NOEC (*Daphnia magna*): 0.069 mg/L;EC<sub>50</sub> (*Daphnia magna*, 48 h): 0.48 mg/L.



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 9/11

**Persistence and degradability:** It has no persistence and is considered rapidly degradable.

Information regarding to:

- Trimethylolpropane triacrylate:

Degradation rate: 82 to 90% in 28 days.

- Methyl isobutyl ketone:

Biodegradation rate: 83% in 28 days.

- Glycerol, propoxylated, esters with acrylic acid:

Degradation rate: 72 - 85% in 28 days.

- 2-Hydroxy-2-methylpropiophenone:

Degradation rate: 90 - 100% in 28 days.

- Butyl acetate:

Degradation rate: 83% after 28 days.

- 2-methoxy-1-methylethyl acetate:

Degradation rate: 90% in 28 days.

- Xylene:

Degradation rate: 98% in 28 days.

- Methyl benzoylformate:

Degradation rate: 90-100% in 28 days.

- 4-methoxyphenol:

Degradation Rate: &gt;80% in 28 days.

- Ethoxylated trimethylolpropane triacrylate:

Degradation rate: 58-61% in 28 days.

**Bioaccumulative potential:** It is not expected to have a high bioaccumulative potential.

**Mobility in soil:** Not determined.

**Other adverse effects:** No other environmental effects known.

**SECTION 13: DISPOSAL CONSIDERATIONS****Disposal methods**

Must be disposed of as waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.

Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

**SECTION 14: TRANSPORT INFORMATION**

**Road:** UN - United Nations: Model Regulations:  
• Recommendations on the Transport of Dangerous Goods.

**UN number:** Not classified as hazardous for the road transportation.

**Environmental hazards:** The product is not considered dangerous for the environment for land transport.

**Railway regulations:** COTIF - Convention concerning International Carriage by Rail:  
• Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.

**UN number:** Not classified as dangerous for rail transport.



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 10/11

**Environmental hazards:** The product is not considered dangerous for the environment in rail transport.**Sea:** IMO - International Maritime Organization:  
• IMDG Code - International Maritime Dangerous Goods Code.**UN number:** Not classified as hazardous for water transportation.**Environmental hazards:** It's not considered a marine pollutant for transportation.**Air:** IATA - International Air Transport Association:  
• DGR - Dangerous Goods Regulation.**UN number:** Not classified as dangerous for air transport.**Environmental hazards:** The product is not considered dangerous for the environment for air transport.**Special precautions for user:** Not applicable.**Transport in bulk according to IMO instruments:** Consult regulations:

- International Maritime Organization: MARPOL: Articles, protocols, annexes, unified interpretations of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, consolidated edition. IMO, London, 2006;
- International Maritime Organization: IBC code: International code for the construction and equipment of shipping carrying dangerous chemicals in bulk: With Standards and guidelines relevant to the code. IMO, London, 2007.

**SECTION 15: REGULATORY INFORMATION****Safety, health and environmental regulations specific for the product in question**

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

**SECTION 16: OTHER INFORMATION**

This document was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other products, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

**Change control:**

Version	Manufacture date	Changes
01	02/20/2026	Elaboration

**Abbreviations:**

ACGIH - American Conference of Governmental Industrial Hygienists;  
ATEmix - Acute Toxicity Estimate of the mixture;  
BEI - Biological Exposure Index;  
CAS - Chemical Abstracts Service;  
Er<sub>C50</sub>- Effective concentration that results in a 50% reduction in the growth rate;  
IARC - International Agency for Research on Cancer;



## SAFETY DATA SHEET

**Product:** Paint / Primer Products

Date: 04/20/2021

Pages: 11/11

IDLH - Immediately Dangerous to Life or Health;  
LC<sub>50</sub>- Lethal Concentration 50%;  
NIOSH - National Institute for Occupational Safety and Health;  
NOEC - No Observed Effect Concentration;  
OSHA - Occupational Safety & Health Administration;  
PBT - Persistent, bioaccumulative and toxic;  
PEL - Permissible Exposure Limit;  
REL - Recommended Exposure Limit;  
STEL - Short Term Exposure Limit;  
TLV - Threshold Limit Value;  
TWA - Time Weighted Average;  
UN - United Nations;  
vPvB - Very Persistent and very Bioaccumulative.

**Bibliographic references:**

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2025.

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 10th rev. ed. New York and Geneva: United Nations, 2023.

**Disclaimer:**

USply LLC believes the information contained in this MSDS to be accurate at the time of preparation and has been compiled using sources believed to be reliable. However, USply LLC makes no warranty, either expressed or implied, concerning the accuracy or completeness of the information presented. Therefore, USply LLC will not be liable for claims relating to any party's use of or reliance on information and data contained herein, regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading. It is also the responsibility of the user to comply with local, state, and federal regulations concerning use of this product. It is the further responsibility of the buyer to research and understand up-to-date information on safe methods of storing, handling and disposal of this product.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.